

## DRISCOPEX<sup>®</sup> 3200 Series Conduit & Casing Dimensions

| Dimensions, Inches (IPS sizes) DR-9 |            |              |            |                 |
|-------------------------------------|------------|--------------|------------|-----------------|
| Nominal Size                        | Average OD | Minimum Wall | Minimum ID | Weight (# / ft) |
| 1 ¼                                 | 1.660      | 0.184        | 1.239      | 0.37            |
| 1 ½                                 | 1.900      | 0.211        | 1.419      | 0.49            |
| 2                                   | 2.375      | 0.264        | 1.761      | 0.76            |
| 3                                   | 3.500      | 0.389        | 2.596      | 1.66            |
| 4                                   | 4.500      | 0.500        | 3.338      | 2.74            |
| 5                                   | 5.563      | 0.618        | 4.126      | 4.18            |
| 6                                   | 6.625      | 0.736        | 4.914      | 5.93            |
| 8                                   | 8.625      | 0.958        | 6.397      | 10.05           |
| 10                                  | 10.750     | 1.194        | 7.973      | 15.62           |
| 12                                  | 12.750     | 1.417        | 9.456      | 21.97           |
| 14                                  | 14.000     | 1.556        | 10.383     | 26.49           |
| 16                                  | 16.000     | 1.778        | 11.867     | 34.60           |
| 18                                  | 18.000     | 2.000        | 13.350     | 43.79           |
| 20                                  | 20.000     | 2.222        | 14.833     | 54.06           |
| 22                                  | 22.000     | 2.444        | 16.317     | 65.41           |
| 24                                  | 24.000     | 2.667        | 17.800     | 77.85           |

| Dimensions, Inches (IPS sizes) DR-11 |            |              |            |                 |
|--------------------------------------|------------|--------------|------------|-----------------|
| Nominal Size                         | Average OD | Minimum Wall | Minimum ID | Weight (# / ft) |
| 1 ¼                                  | 1.660      | 0.151        | 1.316      | 0.31            |
| 1 ½                                  | 1.900      | 0.173        | 1.506      | 0.41            |
| 2                                    | 2.375      | 0.216        | 1.871      | 0.64            |
| 3                                    | 3.500      | 0.318        | 2.757      | 1.39            |
| 4                                    | 4.500      | 0.409        | 3.545      | 2.29            |
| 5                                    | 5.563      | 0.506        | 4.382      | 3.51            |
| 6                                    | 6.625      | 0.602        | 5.219      | 4.97            |
| 8                                    | 8.625      | 0.784        | 6.794      | 8.43            |
| 10                                   | 10.750     | 0.977        | 8.468      | 13.09           |
| 12                                   | 12.750     | 1.159        | 10.044     | 18.41           |
| 14                                   | 14.000     | 1.273        | 11.028     | 22.20           |
| 16                                   | 16.000     | 1.455        | 12.604     | 28.99           |
| 18                                   | 18.000     | 1.636        | 14.179     | 36.70           |
| 20                                   | 20.000     | 1.818        | 15.755     | 45.30           |
| 22                                   | 22.000     | 2.000        | 17.330     | 54.82           |
| 24                                   | 24.000     | 2.182        | 18.905     | 65.24           |

| Dimensions, Inches (IPS sizes) DR-13.5 |            |              |            |                 |
|----------------------------------------|------------|--------------|------------|-----------------|
| Nominal Size                           | Average OD | Minimum Wall | Minimum ID | Weight (# / ft) |
| 1 ¼                                    | 1.660      | 0.123        | 1.380      | 0.26            |
| 1 ½                                    | 1.900      | 0.141        | 1.579      | 0.34            |
| 2                                      | 2.375      | 0.176        | 1.962      | 0.53            |
| 2 ½                                    | 2.875      | 0.213        | 2.375      | 0.78            |
| 3                                      | 3.500      | 0.259        | 2.891      | 1.15            |
| 4                                      | 4.500      | 0.333        | 3.718      | 1.91            |
| 5                                      | 5.563      | 0.412        | 4.596      | 2.91            |
| 6                                      | 6.625      | 0.491        | 5.473      | 4.13            |

NOTICE: This data sheet provides typical physical property information for polyethylene resins used to manufacture PERFORMANCE PIPE polyethylene piping products. It is intended for comparing polyethylene piping resins. It is not a product specification, and it does not establish minimum or maximum values or manufacturing tolerances for resins or for piping products. These typical physical property values were determined using compression-molded plaques prepared from resin. Values obtained from tests of specimens taken from piping products can vary from these typical values. Performance Pipe has made every reasonable effort to ensure the accuracy of this data sheet, but this data sheet may not provide all necessary information, particularly with respect to special or unusual applications. This data sheet may be changed from time to time without notice. Contact Performance Pipe to determine if you have the most recent edition.

| Dimensions, Inches (IPS sizes) DR-15.5 |            |              |            |                 |
|----------------------------------------|------------|--------------|------------|-----------------|
| Nominal Size                           | Average OD | Minimum Wall | Minimum ID | Weight (# / ft) |
| 3                                      | 3.500      | 0.226        | 2.968      | 1.02            |
| 4                                      | 4.500      | 0.290        | 3.816      | 1.68            |

| Dimensions, Inches (IPS sizes) DR-17 |            |              |            |                 |
|--------------------------------------|------------|--------------|------------|-----------------|
| Nominal Size                         | Average OD | Minimum Wall | Minimum ID | Weight (# / ft) |
| 6                                    | 6.625      | 0.390        | 5.703      | 3.34            |
| 8                                    | 8.625      | 0.507        | 7.425      | 5.66            |
| 10                                   | 10.750     | 0.632        | 9.254      | 8.79            |
| 12                                   | 12.750     | 0.750        | 10.976     | 12.36           |
| 14                                   | 14.000     | 0.824        | 12.052     | 14.90           |
| 16                                   | 16.000     | 0.941        | 13.774     | 19.47           |
| 18                                   | 18.000     | 1.059        | 15.496     | 24.64           |
| 20                                   | 20.000     | 1.176        | 17.218     | 30.42           |
| 22                                   | 22.000     | 1.294        | 18.939     | 36.81           |
| 24                                   | 24.000     | 1.412        | 20.661     | 43.80           |

| Dimensions, Inches (Schedule 40) |            |              |            |                 |
|----------------------------------|------------|--------------|------------|-----------------|
| Nominal Size                     | Average OD | Minimum Wall | Minimum ID | Weight (# / ft) |
| 1                                | 1.315      | 0.133        | 1.004      | 0.22            |
| 1 ¼                              | 1.660      | 0.140        | 1.335      | 0.29            |
| 1 ½                              | 1.900      | 0.145        | 1.564      | 0.35            |
| 2                                | 2.375      | 0.154        | 2.021      | 0.47            |
| 2 ½                              | 2.875      | 0.203        | 2.414      | 0.74            |
| 3                                | 3.500      | 0.216        | 3.008      | 0.97            |
| 4                                | 4.500      | 0.237        | 3.961      | 1.39            |
| 6                                | 6.625      | 0.280        | 5.986      | 2.44            |

| Dimensions, Inches (Schedule 80) |            |              |            |                 |
|----------------------------------|------------|--------------|------------|-----------------|
| Nominal Size                     | Average OD | Minimum Wall | Minimum ID | Weight (# / ft) |
| 1                                | 1.315      | 0.179        | 0.910      | 0.28            |
| 1 ¼                              | 1.660      | 0.191        | 1.227      | 0.38            |
| 1 ½                              | 1.900      | 0.200        | 1.446      | 0.47            |
| 2                                | 2.375      | 0.218        | 1.881      | 0.64            |
| 2 ½                              | 2.875      | 0.276        | 2.250      | 0.98            |
| 3                                | 3.500      | 0.300        | 2.820      | 1.32            |
| 4                                | 4.500      | 0.337        | 3.737      | 1.92            |
| 6                                | 6.625      | 0.432        | 5.646      | 3.67            |

| Dimensions, Inches SIDR 11.5 |            |              |            |                 |
|------------------------------|------------|--------------|------------|-----------------|
| Nominal Size                 | Average OD | Minimum Wall | Minimum ID | Weight (# / ft) |
| 1 ¼                          | 1.640      | 0.120        | 1.360      | 0.25            |
| 1 ½                          | 1.910      | 0.140        | 1.590      | 0.34            |
| 2                            | 2.449      | 0.180        | 2.047      | 0.56            |
| 3                            | 3.634      | 0.267        | 3.038      | 1.23            |
| 4                            | 4.768      | 0.350        | 3.991      | 2.12            |
| 6                            | 7.182      | 0.527        | 6.030      | 4.81            |

