

DRISCOPEX[®] 3100 Series Conduit & Casing Dimensions

Dimensions, Inches (IPS sizes) DR-9				
Nominal Size	Average OD	Minimum Wall	Minimum ID	Weight (# / ft)
1	1.315	0.146	0.971	0.23
1 ¼	1.660	0.184	1.236	0.37
1 ½	1.900	0.211	1.416	0.49
2	2.375	0.264	1.771	0.76
2 ½	2.875	0.319	2.149	1.12
3	3.500	0.389	2.616	1.66
4	4.500	0.500	3.360	2.74
5	5.563	0.618	4.154	4.18
6	6.625	0.736	4.947	5.93
8	8.625	0.958	6.422	10.05
10	10.750	1.194	8.028	15.62
12	12.750	1.417	9.512	21.97

Dimensions, Inches (IPS sizes) DR-17				
Nominal Size	Average OD	Minimum Wall	Minimum ID	Weight (# / ft)
1	1.315	0.077	1.109	0.13
1 ¼	1.660	0.098	1.412	0.21
1 ½	1.900	0.112	1.624	0.27
2	2.375	0.140	2.043	0.43
2 ½	2.875	0.169	2.485	0.63
3	3.500	0.206	3.028	0.93
4	4.500	0.265	3.886	1.54
5	5.563	0.327	4.806	2.35
6	6.625	0.390	5.721	3.34
8	8.625	0.507	7.434	5.66
10	10.750	0.632	9.286	8.79
12	12.750	0.750	11.006	12.36

Dimensions, Inches (IPS sizes) DR-11				
Nominal Size	Average OD	Minimum Wall	Minimum ID	Weight (# / ft)
1	1.315	0.120	1.023	0.20
1 ¼	1.660	0.151	1.306	0.31
1 ½	1.900	0.173	1.500	0.41
2	2.375	0.216	1.879	0.64
2 ½	2.875	0.261	2.279	0.94
3	3.500	0.318	2.776	1.39
4	4.500	0.409	3.564	2.29
5	5.563	0.506	4.424	3.51
6	6.625	0.602	5.245	4.97
8	8.625	0.784	6.812	8.43
10	10.750	0.977	8.514	13.09
12	12.750	1.159	10.090	18.41

Dimensions, Inches (Schedule 40)				
Nominal Size	Average OD	Minimum Wall	Minimum ID	Weight (# / ft)
1	1.315	0.133	1.003	0.22
1 ¼	1.660	0.140	1.334	0.29
1 ½	1.900	0.145	1.564	0.35
2	2.375	0.154	2.019	0.47
2 ½	2.875	0.203	2.409	0.74
3	3.500	0.216	3.004	0.97
4	4.500	0.237	3.950	1.39
5	5.563	0.258	4.960	1.88
6	6.625	0.280	5.967	2.44
8	8.625	0.322	7.846	3.68
10	10.750	0.365	9.884	5.22
12	12.750	0.406	11.776	6.90

Dimensions, Inches (IPS sizes) DR-13.5				
Nominal Size	Average OD	Minimum Wall	Minimum ID	Weight (# / ft)
1	1.315	0.097	1.069	0.16
1 ¼	1.660	0.123	1.362	0.26
1 ½	1.900	0.141	1.566	0.34
2	2.375	0.176	1.969	0.53
2 ½	2.875	0.213	2.387	0.78
3	3.500	0.259	2.908	1.15
4	4.500	0.333	3.734	1.91
5	5.563	0.412	4.616	2.91
6	6.625	0.491	5.495	4.13
8	8.625	0.639	7.136	7.00
10	10.750	0.796	8.918	10.88
12	12.750	0.944	10.572	15.30

Dimensions, Inches (Schedule 80)				
Nominal Size	Average OD	Minimum Wall	Minimum ID	Weight (# / ft)
1	1.315	0.179	0.903	0.28
1 ¼	1.660	0.191	1.220	0.38
1 ½	1.900	0.200	1.440	0.47
2	2.375	0.218	1.875	0.64
2 ½	2.875	0.276	2.245	0.98
3	3.500	0.300	2.816	1.32
4	4.500	0.337	3.726	1.92
5	5.563	0.375	4.698	2.67
6	6.625	0.432	5.627	3.67

Dimensions, Inches (IPS sizes) DR-15.5				
Nominal Size	Average OD	Minimum Wall	Minimum ID	Weight (# / ft)
1	1.315	0.084	1.095	0.14
1 ¼	1.660	0.107	1.394	0.23
1 ½	1.900	0.123	1.602	0.30
2	2.375	0.153	2.017	0.47
2 ½	2.875	0.185	2.449	0.68
3	3.500	0.226	2.982	1.02
4	4.500	0.290	3.830	1.68
5	5.563	0.359	4.734	2.56
6	6.625	0.427	5.639	3.64
8	8.625	0.556	7.322	6.16
10	10.750	0.694	9.148	9.58
12	12.750	0.823	10.842	13.47

NOTICE: This data sheet provides typical physical property information for polyethylene resins used to manufacture PERFORMANCE PIPE polyethylene piping products. It is intended for comparing polyethylene piping resins. It is not a product specification, and it does not establish minimum or maximum values or manufacturing tolerances for resins or for piping products. These typical physical property values were determined using compression-molded plaques prepared from resin. Values obtained from tests of specimens taken from piping products can vary from these typical values. Performance Pipe has made every reasonable effort to ensure the accuracy of this data sheet, but this data sheet may not provide all necessary information, particularly with respect to special or unusual applications. This data sheet may be changed from time to time without notice. Contact Performance Pipe to determine if you have the most recent edition.

