



Revised 03-17-2008

DIPS Size and Dimension Data

PE3608 (PE3408)

DriscoPlex[®] Municipal & Industrial & Energy Series/DIPS Pipe Data

Pressure Ratings are calculated using 0.50 design factor for HDS at 73°F as listed in PPI TR-4 for PE 3608 materials.
Temperature, Chemical, and Environmental use considerations may require use of additional design factors.

Pressure Rating		255 psi DR 7.3			200 psi DR 9.0			160 psi DR 11.0			130 psi DR 13.5			
DIPS Pipe Size	Nominal OD (in)	Minimum Wall (in)	Average ID (in)	Weight (lbs/ft)	Minimum Wall (in)	Average ID (in)	Weight (lbs/ft)	Minimum Wall (in)	Average ID (in)	Weight (lbs/ft)	Minimum Wall (in)	Average ID (in)	Weight (lbs/ft)	DIPS Pipe Size
4"	4.800	0.658	3.405	3.72	0.533	3.670	3.11	0.436	3.876	2.61	0.356	4.045	2.17	4"
6"	6.900	0.945	4.897	7.69	0.767	5.274	6.43	0.627	5.571	5.39	0.511	5.817	4.48	6"
8"	9.050	1.240	6.421	13.22	1.006	6.917	11.07	0.823	7.305	9.28	0.670	7.630	7.71	8"
10"	11.100	1.521	7.875	19.89	1.233	8.486	16.65	1.009	8.961	13.95	0.822	9.357	11.60	10"
12"	13.200	1.808	9.367	28.13	1.467	10.090	23.55	1.200	10.656	19.73	0.978	11.127	16.40	12"
14"	15.300	2.096	10.856	37.79	1.700	11.696	31.64	1.391	12.351	26.51	1.133	12.898	22.03	14"
16"	17.400	2.384	12.346	48.88	1.933	13.302	40.92	1.582	14.046	34.29	1.289	14.667	28.49	16"
18"	19.500	2.671	13.837	61.39	2.167	14.906	51.39	1.773	15.741	43.07	1.444	16.439	35.78	18"
20"	21.600				2.400	16.512	63.05	1.964	17.436	52.84	1.600	18.208	43.91	20"
24"	25.800				2.867	19.722	89.96	2.345	20.829	75.39	1.911	21.749	62.64	24"
30"	32.000							2.909	25.833	115.98	2.370	26.976	96.37	30"
†36"	38.300							3.482	30.918	166.14	2.837	32.286	138.05	†36"
†42"	44.500										3.296	37.512	186.36	†42"

Pressure Rating		100 psi DR 17.0			80 psi DR 21.0			65 psi DR 26.0			50 psi DR 32.5			
DIPS Pipe Size	Nominal OD (in)	Minimum Wall (in)	Average ID (in)	Weight (lbs/ft)	Minimum Wall (in)	Average ID (in)	Weight (lbs/ft)	Minimum Wall (in)	Average ID (in)	Weight (lbs/ft)	Minimum Wall (in)	Average ID (in)	Weight (lbs/ft)	DIPS Pipe Size
4"	4.800	0.282	4.202	1.75	0.229	4.315	1.44							4"
6"	6.900	0.406	6.039	3.62	0.329	6.203	2.97	0.265	6.338	2.42	0.212	6.451	1.95	6"
8"	9.050	0.532	7.922	6.23	0.431	8.136	5.11	0.348	8.312	4.17	0.278	8.461	3.36	8"
10"	11.100	0.653	9.716	9.37	0.529	9.979	7.68	0.427	10.195	6.27	0.342	10.375	5.06	10"
12"	13.200	0.776	11.555	13.25	0.629	11.867	10.86	0.508	12.123	8.86	0.406	12.339	7.15	12"
14"	15.300	0.900	13.392	17.80	0.729	13.755	14.59	0.588	14.053	11.91	0.471	14.301	9.61	14"
16"	17.400	1.024	15.229	23.02	0.829	15.643	18.87	0.669	15.982	15.40	0.535	16.266	12.42	16"
18"	19.500	1.147	17.068	28.92	0.929	17.531	23.70	0.750	17.910	19.34	0.600	18.228	15.60	18"
20"	21.600	1.271	18.905	35.48	1.029	19.419	29.08	0.831	19.838	23.73	0.665	20.190	19.15	20"
24"	25.800	1.518	22.582	50.62	1.229	23.195	41.50	0.992	23.697	33.86	0.794	24.117	27.32	24"
30"	32.000	1.882	28.010	77.87	1.524	28.769	63.84	1.231	29.390	52.09	0.985	29.912	42.02	30"
†36"	38.300	2.253	33.524	111.55	1.824	34.433	91.44	1.473	35.177	74.61	1.178	35.803	60.20	†36"
†42"	44.500	2.618	38.950	150.59	2.119	40.008	123.45	1.712	40.871	100.73	1.369	41.598	81.27	†42"

Pipe weights are calculated in accordance with PPI TR-7. Average inside diameter is calculated using Nominal OD and Minimum Wall plus 6% for use in estimating fluid flows. Actual ID will vary. When designing components to fit the pipe ID, refer to pipe dimensions and tolerances in the applicable pipe manufacturing specification.

†OD available upon special request -- Check with your performance Pipe contact for availability of dimensions not listed.

Visit www.performancepipe.com for the most current literature.