

JCM 307 Fabricated Reducing Flanged Coupling Adapters

The JCM 307 Reducing Fabricated Flanged Coupling Adapter combines the versatile JCM Ductile Iron Coupling system with an increaser or reducer fabricated flanged end to provide a fitting which allows for pipe misalignment, less critical pipe end preparation and ease of equipment installation and removal. The 307 FCAs are easily adapted from one type of pipe to another with the simple JCM Transition Gasket system. These FCAs simplify installations on larger A/C pipe and are available in the hard to find 10" and 12" sizes.



307 FLANGED REDUCING COUPLING ADAPTERS

NOM. PIPE SIZE (IN.)	COUPLING O.D. RANGE (IN.)	CATALOG NUMBER	(X) ADD REQUIRED FLANGE SIZE	OVERALL LENGTH (IN.)
3	3.50	307-0350	X	12
	3.80 - 4.17	307-0396	X	12
4	4.50	307-0450	X	12
	4.80 - 5.10	307-0480	X	12
	5.10 - 5.40	307-0535	X	12
6	6.63	307-0663	X	12
	6.90 - 7.20	307-0690	X	12
	7.20 - 7.55	307-0740	X	12
8	8.63	307-0863	X	12
	9.05 - 9.40	307-0905	X	12
	9.40 - 9.75	307-0960	X	12
10	10.75	307-1075	X	12
	11.10 - 11.40	307-1110	X	12
	11.60 - 12.05	307-1200	X	12
12	12.75	307-1275	X	12
	13.20 - 13.50	307-1320	X	12
	13.92 - 14.40	307-1420	X	12

Epoxy coating and stainless steel bolts available.

Integral retainer set screws are available as an extra. Add (R) to end of catalog number. Price on application.

NOTE: Restraining set screws are not for use on Asbestos Cement, HDPE or PVC pipe.

NOTE: Applications in which pipe may move out of the coupling, proper anchorage of the pipe must be provided.

