

Rubber Hose



180 HR

High temperature abrasion resistant suction hose.

Temp. Range: -40°F to 220°F

Applications: Heavy duty suction applications where higher temperature and abrasion are factors such as vacuum trucks or the handling of fly ash, crushed rock, sand, pea gravel or cement powder.

Construction: EPDM rubber, polyethylene helix, metal helical wire, smooth bore, corrugated O.D.

Features: Lightweight and flexible. Integral wire helix can be grounded. External helix provides easy drag. Rated up to 220°F.

Inside Dia. Inches	Outside Dia. Inches	Pitch Dia. Inches	Minimum Bend Radius 72°F, Inches	Working Pressure 72°F, P.S.I.	Vacuum Rating 72°F, In/Hg	Weight Lbs/Ft	Standard Length Ft
4	4.69	.65	5.5	30	29.8	1.75	50,100
6	6.83	.87	9.8	30	28.0	3.46	50,100
8	9.13	.87	15.0	30	27.0	6.00	50

Rubber Hose



180 MV

Abrasion resistant medium-duty suction and discharge hose.

Temp. Range: -40°F to 140°F

Applications: Designed for numerous applications such as grain and roof vacuums.

Construction: SBR rubber with carbon black, rigid PVC helix, smooth bore, corrugated O.D.

Inside Dia. Inches	Outside Dia. Inches	Pitch Dia. Inches	Minimum Bend Radius 72°F, Inches	Working Pressure 72°F, P.S.I.	Vacuum Rating 72°F, In/Hg	Weight Lbs/Ft	Standard Length Ft
5	5.75	.87	5.0	8	18.0	2.00	50,100
6	6.73	.87	9.0	8	18.0	2.70	50,100