

# Rubber Hose

## 220 RS

*All weather suction and discharge hose.*

**Temp. Range:** -40°F to 140°F

**Applications:** Heavy duty liquid suction hose for use in construction dewatering, liquid waste, cesspool cleaning, septic handling, agricultural applications and marine use.

**Construction:** SBR rubber, rigid PVC helix, smooth bore, smooth O.D.

Inside Dia. Inches	Outside Dia. Inches	Pitch Dia. Inches	Minimum Bend Radius 72°F, Inches	Working Pressure 72°F, P.S.I.	Vacuum Rating 72°F, In/Hg	Weight Lbs/Ft	Standard Length Ft
1½	1.85	.35	3.0	50	29.8	.50	100
2	2.40	.39	4.0	50	29.8	.74	100
2½	2.99	.56	5.0	50	29.8	1.01	100
3	3.50	.59	6.0	43	29.8	1.30	100
4	4.57	.65	9.0	38	29.8	2.01	100
6	6.69	.87	15.0	23	28.0	3.37	60,100



## 300 EPDM

*All weather suction and discharge hose.*

**Temp. Range:** -40°F to 140°F

**Applications:** Heavy duty liquid suction hose for use in construction dewatering, liquid waste, cesspool cleaning, septic handling, agricultural applications and marine use.

**Construction:** EPDM rubber, polyethylene helix, smooth bore, corrugated O.D.

**Features:** Lightweight and flexible. External helix provides for easy drag. Resistant to agricultural chemicals.

Inside Dia. Inches	Outside Dia. Inches	Pitch Dia. Inches	Minimum Bend Radius 72°F, Inches	Working Pressure 72°F, P.S.I.	Vacuum Rating 72°F, In/Hg	Weight Lbs/Ft	Standard Length Ft
1	1.34	.30	1.9	50	29.8	.23	100
1¼	1.65	.33	3.2	50	29.8	.34	100
1½	1.84	.35	3.2	50	29.8	.40	100
2	2.43	.39	5.2	50	29.8	.67	100
2½	2.99	.56	5.6	50	29.8	.92	100
3	3.52	.59	7.1	43	29.8	1.10	100
4	4.61	.65	11.0	38	29.8	1.84	100
6	6.81	.87	20.0	23	28.0	3.07	60,100

