

Duct Hose



620 WD

General ducting and blower hose with metal wire helix.

Temp. Range: -40°F to 220°F

Applications: General ducting and blower applications. For use with light-weight abrasives such as sawdust, grass clippings, street refuse and cotton pickers.

Construction: EPDM rubber, metal wire helix, smooth bore, slightly corrugated O.D.

Features: Rated to 220°F. Abrasion resistant yet very flexible. 100% rubber sidewall (no fabric).

Inside Dia. Inches	Outside Dia. Inches	Pitch Dia. Inches	Minimum Bend Radius 72°F, Inches	Working Pressure 72°F, P.S.I.	Vacuum Rating 72°F, In/Hg	Weight Lbs/Ft	Standard Length Ft
2	2.36	.43	2.0	9	12.0	.40	50
2½	3.00	.58	3.0	12	9.0	.44	50
3	3.37	.60	3.0	12	8.0	.55	50
4	4.39	.65	4.0	9	6.0	.73	50
5	5.43	.88	5.0	7	5.0	.84	50
6	6.36	.87	6.0	6	4.0	1.04	50
7	7.32	.89	7.0	5	4.0	1.17	50
8	8.35	.92	8.0	4	4.0	1.38	50
10	10.45	1.02	10.0	3	4.0	2.40	50
12	12.40	1.20	12.0	3	4.0	2.50	25

620 WD WS

General ducting and blower hose with metal wire helix and external wear strip.

Temp. Range: -40°F to 220°F

Applications: Same as 620 WD, but external wearstrip makes it ideal for “light dragging” applications.

Construction: EPDM rubber, metal wire helix, wearstrip, smooth bore, corrugated O.D.



Inside Dia. Inches	Outside Dia. Inches	Pitch Dia. Inches	Minimum Bend Radius 72°F, Inches	Working Pressure 72°F, P.S.I.	Vacuum Rating 72°F, In/Hg	Weight Lbs/Ft	Standard Length Ft
2½	3.11	.58	3.0	12	9.0	.48	50
3	3.48	.60	3.0	12	8.0	.61	50
4	4.57	.65	4.0	9	6.0	.85	50
5	5.61	.88	5.0	7	5.0	.90	50
6	6.54	.87	6.0	6	4.0	1.17	50
7	7.48	.89	7.0	5	4.0	1.27	50
8	8.54	.92	8.0	4	4.0	1.50	50
10	10.69	1.02	10.0	3	4.0	2.67	50
12	12.60	1.20	12.0	3	4.0	2.80	25