

Duct Hose



Duct Hose



630 ED

Medium-duty blower and ducting hose.

Temp. Range: -40°F to 158°F

Applications: Medium-duty blower and ducting applications such as hay baling, street refuse, grain dust, cotton pickers, wood chips, straw blowing, leaf and grass collection.

Construction: EPDM rubber, polypropylene helix, smooth bore, corrugated O.D.

Features: Thicker sidewall for more abrasion resistance. External helix acts as a scuff guard. 100% rubber sidewall (no fabric).

Inside Dia. Inches	Outside Dia. Inches	Pitch Dia. Inches	Minimum Bend Radius 72°F, Inches	Working Pressure 72°F, P.S.I.	Vacuum Rating 72°F, In/Hg	Weight Lbs/Ft	Standard Length Ft
2	2.36	.39	3.5	—	—	.31	50
2 ¹ / ₂	2.89	.56	3.5	—	—	.38	50
3	3.43	.59	4.0	—	—	.49	50
4	4.53	.67	4.0	—	—	.70	50
6	6.56	.83	6.0	—	—	1.05	50
8	8.66	.87	8.0	—	—	1.46	50

660 YD

Heavy-duty duct hose with “safety yellow” helix for high visibility.

Temp. Range: -40°F to 158°F

Applications: Heavy-duty ducting applications such as duct cleaning, commercial grass and leaf collection, cement dust recovery for floor finishing, blast cabinet dust collection systems, and grain auger downspouts.

Construction: EPDM rubber, polypropylene helix, smooth bore, corrugated O.D.

Features: Smooth bore for higher laminar flow. Extra heavy-duty “safety yellow” helix for high visibility and superior external abrasion resistance for “dragging” applications. 100% rubber sidewall (no fabric).

Inside Dia. Inches	Outside Dia. Inches	Pitch Dia. Inches	Minimum Bend Radius 72°F, Inches	Working Pressure 72°F, P.S.I.	Vacuum Rating 72°F, In/Hg	Weight Lbs/Ft	Standard Length Ft
4	4.57	.67	4.0	9	6.0	.79	50
5	5.53	.87	5.0	7	5.0	.83	50
6	6.57	.83	6.0	6	4.0	1.26	50
8	8.72	.87	8.0	4	4.0	1.92	50
10	10.83	1.06	10.0	4	4.0	2.38	50
12	12.73	1.18	12.0	3	3.0	2.65	25