

PVC Hose



130 Y (yellow), **130 B** (black, limited quantities)
Oil resistant PVC suction and discharge hose.

Temp. Range: -13°F to 140°F

Applications: Heavy-duty suction and discharge of light oils and animal fats.

Construction: Flexible oil-resistant PVC, rigid PVC helix, smooth bore, smooth O.D.

Note: Not intended for handling of gasoline.

Inside Dia. Inches	Outside Dia. Inches	Pitch Dia. Inches	Minimum Bend Radius 72°F, Inches	Working Pressure 72°F, P.S.I.	Vacuum Rating 72°F, In/Hg	Weight Lbs/Ft	Standard Length Ft
1	1.25	.22	1.9	86	29.8	.26	100
1 ¹ / ₄	1.52	.26	2.7	79	29.8	.37	100
1 ¹ / ₂	1.81	.30	2.8	72	29.8	.44	100
2	2.38	.33	3.9	72	29.8	.74	100
2 ¹ / ₂	2.92	.37	5.0	72	29.8	1.01	100
3	3.41	.37	7.0	62	29.8	1.21	100
4	4.50	.43	9.1	55	29.8	2.01	100

PVC Hose



155 GY

Heavy-duty PVC blower and ducting hose.

Temp. Range: -13°F to 140°F

Applications: Heavy-duty PVC blower and ducting hose for grass, leaves, dust, and fumes.

Construction: Flexible PVC, rigid PVC helix, smooth bore, corrugated O.D.

Inside Dia. Inches	Outside Dia. Inches	Pitch Dia. Inches	Minimum Bend Radius 72°F, Inches	Working Pressure 72°F, P.S.I.	Vacuum Rating 72°F, In/Hg	Weight Lbs/Ft	Standard Length Ft
1 ¹ / ₂	1.79	.35	1.5	20	20.0	.26	100
2	2.31	.39	2.5	15	18.0	.39	100
2 ¹ / ₂	2.85	.54	3.0	15	15.0	.44	100
3	3.39	.56	3.5	15	15.0	.70	100
4	4.60	.65	4.5	15	15.0	1.43	100
5	5.52	.87	8.8	12	12.0	1.87	100
6	6.52	.87	9.0	11	10.0	2.32	100
8	8.85	.91	14.0	10	9.0	4.03	100