



P32 In-Line Check Valves

BODY MATERIALS: PVC

SIZES: 1/2" - 2"

END TYPES: Threaded, Socket

SEAL: EPDM

TEST PRESSURE: 225 PSI


WORKING PRESSURE: 150 PSI

Check Valves Foot Valves	Body	Style	Ends	Seals
P32	Schd 40 PVC	Spring Check	IPS	EPDM
P32S	Schd 40 PVC	Spring Check	Socket	EPDM



- Maintenance free operation.
- Minimum flow pressure 2 PSI.
- Use any place to stop backflow and siphoning-swimming pools, hot tubs, spas, solar equipment, industrial applications, agricultural irrigation, etc.

SIZE		15mm	20mm	25mm	32mm	40mm	50mm
Nom.		(1/2")	(3/4")	(1")	(1-1/4")	(1-1/2")	(2")
thd./	NPT	14	14	11.5	11.5	11.5	11.5
in	BSPT	14	14	11	11	11	11
JIS	d2	21.7	25.7	31.67	37.57	47.54	59.44
	d1	22.3	26.3	32.33	38.43	48.46	60.56
ANSI	d2	21.23	26.57	33.27	42.04	48.11	60.17
	d1	21.54	26.87	33.65	42.42	48.56	60.63
DIN	d2	20.1	25.1	32.1	40.1	50.1	63.1
	d1	20.3	25.3	32.3	40.3	50.3	63.3
d		17	21	28	35	39	52
D		56	56	73	91	91	107
D1		35	35	45	52	60	73
D2		38	38	48	55	63	76
H		105	105	133	151	151	178
I		17.48	18.26	22.22	23.82	27.38	29.36



NO.	PART	MATERIAL	Q'TY
1	UPPER BODY	PVC	1
2	LOWER BODY	PVC	1
3	SPIGOT	PVC	1
4	CONNECTOR SEAT	PVC	1
5	SPRING	SUS 304	1
6	SEAL	EPDM	1

AMERICAN VALVE STATEMENT OF WARRANTY & LIMITATION OF WARRANTY

American Valve warrants, to its initial purchaser only, that its products which are delivered to this initial purchaser will be the kind described in the order or price list and will be free of defects in workmanship or material for a period of one year from the date of delivery to you, our initial purchaser.

Should any failure to conform to this warranty appear within one year after the date of the initial delivery to our initial purchaser, American Valve will, upon written notification thereof and substantiation that the goods have been stored, installed, maintained and operated in accordance with American Valve's recommendation and standard industry practice, correct such defects by suitable repair or replacement at American Valve's own expense. If any valve alleged to be defective, is returned to our factory at Greensboro, NC, it will be examined and, if found to be defective under the warranty, it will be replaced at no charge.

THIS WARRANTY IS EXCLUSIVE AND IS IN LIEU OF ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHER WARRANTY OF QUALITY, WHETHER EXPRESS OR IMPLIED, EXCEPT THE WARRANTY OF TITLE AND AGAINST PATENT INFRINGEMENT. Correction of non-conformities, in the manner and for the period of time provided above, shall constitute fulfillment of all liabilities of American Valve to our initial purchaser, with respect to the goods, whether based on contract, negligence, strict tort or otherwise, it is the intention of American Valve that no warranty of any kind, whether express or implied, shall pass through our initial purchaser to any other person or corporation.

LIMITATION OF LIABILITY: American Valve SHALL NOT UNDER ANY CIRCUMSTANCES BE LIABLE FOR SPECIAL OR CONSEQUENTIAL DAMAGES SUCH AS, BUT NOT LIMITED TO, DAMAGES OR LOSS OF OTHER PROPERTY OR EQUIPMENT, LOSS OF PROFITS, OR REVENUE, COST OF CAPITAL, COST OF PURCHASED OR REPLACEMENT GOODS, OR CLAIMS OF CUSTOMERS OF OUR INITIAL PURCHASER. THE REMEDIES OF OUR INITIAL PURCHASER, AND ALL OTHERS, SET FORTH HEREIN ARE EXCLUSIVE, AND THE LIABILITY OF AMERICAN VALVE WITH RESPECT TO SAME SHALL NOT, EXCEPT AS EXPRESSLY PROVIDED HEREIN, EXCEED THE PRICE OF GOODS UPON WHICH SUCH LIABILITY IS BASED.



P.O. Box 35229
Greensboro, NC 27425
Phone: 1-800-645-0101
Fax: 1-800-876-0109
<http://www.AmericanValve.com>