



## MOLDED PE SOCKET REDUCER

Available Size Range:

½" CTS - 4" IPS

At Central Plastics we are proud to be recognized as an International leader in the world of manufactured Polyethylene (PE) fittings. With manufacturing facilities located around the world, Central Plastics has been actively involved since the early 1960's in the research and promotion of innovative joining methods for polyethylene piping systems for the natural gas, potable water, wastewater, oilfield, mining landfill, telecommunications and geothermal industries.

With unparalleled expertise focusing on the design and manufacturing of polyethylene fittings, Central Plastics offers the largest, most complete line of polyethylene products, manufactured from a variety of common virgin resins, available in the market. Our substantial vertically integrated manufacturing capabilities allow Central Plastics to exercise complete control of our manufactured products. From design, to "state of the art" manufacturing, to shipping; Central Plastics maintains a high level of product consistency and quality throughout our manufacturing processes.

Central's Molded PE2406 Socket Fusion fittings are manufactured and tested to the requirements of ASTM D2513 and are manufactured for use with pipe conforming to ASTM D2513. Central's PE2406 Socket fittings are molded from a yellow medium density pre-blended virgin resin in accordance with the material specifications listed in ASTM D3350 with a PPI designation of PE2406. All Central Plastics PE2406 Socket Fusion Fittings are manufactured and tested to the requirements of ASTM D2683 and are compatible for heat fusion with any pipe and or fitting manufactured from a like or similar resin.

Central's Molded PE3408 Socket Fusion fittings fully manufactured and tested to the requirements of ASTM D2513 and are manufactured for use with pipe conforming to ASTM D2513 and ASTM F-714. Central's PE3408 Socket fittings are molded from a black high density pre-blended virgin resin in accordance with the material specifications listed in ASTM D3350 with a PPI designation of PE3408. All Central Plastics PE3408 Socket Fusion Fittings are manufactured and tested to the requirements of ASTM D2683 and are compatible for heat fusion with any pipe and or fitting manufactured from a like or similar resin.

### AVAILABLE FEATURES:

- PE2406 fittings are engineered for use on MDPE Pipe
- PE3408 fittings are engineered for use on HDPE Pipe
- Pressure ratings up to SDR7 on most sizes.
- CSA Approved
- Can be used with all socket fusion equipment
- Manufactured in U.S.A.